

600TL Series Loaders

TECHNICAL SPECIFICATIONS

(*)Developed by CNH Engine Corporation • Standard • Optional at extra cost

	610TL- TT45A - 2WD	610TL- TT50A - 2WD	620TL- TT60A - 2WD	620TL- TT60A - 4WD	620TL- TT75A - 2WD	620TL- TT75A - 4WD
Specifications						
Tractor Compatibility	TT45A	TT50A	TT60A	TT60A	TT75A	TT75A
2WD/4WD	2WD	2WD	2WD	4WD	2WD	4WD
Max. lift height, in. (mm)	109.0 (2769)	111.7 (2837)	114.5 (2908)	118.0 (2997)	114.5 (2908)	118.0 (2997)
Dump clearance, in. (mm)	90.3 (2294)	93.0 (2362)	92.5 (2350)	93.0 (2362)	92.5 (2350)	93.0 (2362)
Digging depth, in. (mm)	6.0 (152)	5.5 (140)	5.0 (127)	5.5 (140)	5.0 (127)	5.5 (140)
Lift capacity @ 500 mm from bucket pivot pin, lb. (kg)	1320 (599)	1320 (599)	NA	NA	NA	NA
Lift capacity @ 800 mm from bucket pivot pin, lb. (kg)	NA	NA	2210 (1002)	2150 (975)	2210 (1002)	2150 (975)
Breakout force @ 500 mm from bucket pivot pin, lb.	3400 (1542)	3400 (1542)	NA	NA	NA	NA

(kg)						
Breakout force @ 800 mm from bucket pivot pin, lb. (kg)	NA	NA	4791 (2255)	4520 (2050)	4791 (2255)	4520 (2050)
Reach @ max. lift height, in. (mm)	24.3 (617)	24.3 (617)	34.0 (864)	26.0 (660)	34.0 (864)	26.0 (660)
Bucket rollback angle, degrees	20	20	23	26	23	26
Bucket dump angle, degrees	42	42	45	47	45	47

See product brochure for full specifications and options