

New Holland Sicklebar Mowers

451 456



NEW HOLLAND



Offset wheels on the Model 456 maintain precise tracking to leave a smooth, clean swath.

Smooth cutting and fast, easy hookup

A New Holland sicklebar mower takes the effort out of your cutting chores. It cuts a smooth, fast swath through open fields and makes quick work out of mowing around ponds, buildings and lanes.

The mounted 451 is available with a seven- or nine-foot cutterbar with bolt-on knife sections. The trail-type 456 is only available with a nine-foot cutterbar with bolt-on knife sections. And, both are easy to hook up to your tractor. The mounted Model 451 has an exclusive telescoping yoke that uses tractor power to lift the

mower. No more struggling or straining when it's time to hook up.

Pitmanless drive and tapered roller bearings give you fast, smooth cutting with less wear on the knife assembly and hold-down clips. There's less noise and vibration and no need for register adjustment. A spring-loaded latch ensures fast breakaway should the cutterbar hit an obstruction. The mower relatches when you back up.

Depend on New Holland sicklebar mowers. They provide you with convenience and dependable performance.

Specifications	Model 451	
	seven-foot	nine-foot
Cutterbar length	7'3" (2210 mm)	9'3" (2819 mm)
Overall length	3'11" (1188 mm)	3'11" (1188 mm)
Overall width		
operating	12'5" (3785 mm)	14'5" (4395 mm)
transport	6'2" (1870 mm)	7'2" (2175 mm)
Height		
operating	3'3" (991 mm)	3'3" (991 mm)
transport *	5'8" (1715 mm)	6'8" (2032 mm)
Weight, approximate.....	609 lb (276 kg)	628 lb (285 kg)
Mower drive.....	Heavy-duty V-belt	Heavy-duty V-belt
Knives		
speed	1600 strokes per minute at 540 rpm	
stroke	3.375" (86 mm)	3.375" (86 mm)
Cutterbar		
operating range	15 degrees below horizontal, 35 degrees above horizontal	
Tractor requirement	Fits most CAT I and II 3-point hitch tractors with 540 rpm PTO	

Specifications	Model 456	
	Cutterbar length	9'3" (2819 mm)
Overall length	7'6" (2286 mm)	
Overall width		
operating	15'3" (4648 mm)	
transport	7'2" (2175 mm)	
Height		
operating	3'3" (991 mm)	
transport *	6'8" (2032 mm)	
Weight, approximate	803 lb (364 kg)	
Mower drive	Heavy-duty V-belt	
Knives		
speed	1600 strokes per minute at 540 rpm	
stroke	3.375" (86 mm)	
Cutterbar		
operating range	15 degrees below horizontal, 35 degrees above horizontal	
Tractor requirement	Fits most tractors with standard ASAE drawbar and 540 rpm PTO	

* plus lift range of tractor

LIFTS: Both lifts operable from the tractor seat. Tractor remote ram required for hydraulic lift on Model 456. Tractor power lift is standard on Model 451.



The mounted 451 has an exclusive telescoping yoke that uses tractor power to lift the mower.



Straight-line motion of the drive head provides fast, smooth cutting combined with less wear on the knife assembly and hold-down clips.

YOUR NEW HOLLAND DEALER

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

NEW HOLLAND IS A BRAND OF CNH.
A GLOBAL LEADER IN AGRICULTURAL AND CONSTRUCTION EQUIPMENT AND FINANCIAL SERVICES.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

